

## CAAD12

| SPECIFICATIONS                         | 48        | 50        | 52        | 54        | 56        | 58         | 60         | 63         |
|--|-----------|-----------|-----------|-----------|-----------|------------|------------|------------|
| <b>A</b> TOP TUBE HORIZONTAL (CM/IN)   | 51.0/20.1 | 52.2/20.5 | 53.4/21.0 | 54.7/21.5 | 56.1/22.1 | 57.5/22.6  | 59.1/23.2  | 60.7/23.9  |
| <b>B</b> SEAT TUBE LENGTH (CM/IN)      | 53.5/21.1 | 54.5/21.5 | 56.0/22.0 | 57.0/22.4 | 58.5/23.0 | 60.0/23.6  | 61.5/24.2  | 62.5/24.6  |
| <b>C</b> SEAT TUBE ANGLE EFFECTIVE     | 74.7°     | 74.4°     | 74.1°     | 73.8°     | 73.5°     | 73.2°      | 72.9°      | 72.6°      |
| <b>D</b> HEAD TUBE ANGLE               | 71.5°     | 72.0°     | 72.6°     | 72.9°     | 73.1°     | 73.2°      | 73.3°      | 73.4°      |
| <b>E</b> CHAIN STAY LENGTH (CM/IN)     | 40.5/15.9 | ★         | ★         | ★         | ★         | ★          | 40.7/16.0  | 40.9/16.1  |
| <b>F</b> FORK RAKE (CM/IN)             | 4.5/1.8   | ★         | ★         | ★         | ★         | ★          | ★          | ★          |
| <b>G</b> BOTTOM BRACKET HEIGHT (CM/IN) | 26.6/10.5 | ★         | 26.9/10.6 | ★         | ★         | 27.1/10.7  | ★          | ★          |
| <b>H</b> WHEELBASE (CM/IN)             | 96.3/37.9 | 96.7/38.1 | 97.2/38.3 | 98.0/38.6 | 98.9/38.9 | 100.0/39.4 | 101.3/39.9 | 102.7/40.4 |
| <b>I</b> TRAIL (CM/IN)                 | 6.6/2.6   | 6.3/2.5   | 5.9/2.3   | 5.8/2.3   | 5.6/2.2   | 5.6/2.2    | 5.5/2.2    | 5.4/2.1    |
| <b>J</b> STANDOVER (CM/IN)             | 76.0/29.9 | 77.0/30.3 | 78.2/30.8 | 79.6/31.3 | 81.2/32.0 | 83.1/32.7  | 85.1/33.5  | 87.5/34.4  |
| <b>K</b> BOTTOM BRACKET DROP (CM/IN)   | 7.4/2.9   | ★         | 7.2/2.8   | ★         | ★         | 6.9/2.7    | ★          | ★          |
| <b>L</b> FRONT CENTER (CM/IN)          | 56.5/22.2 | 56.9/22.4 | 57.4/22.6 | 58.1/22.9 | 59.0/23.2 | 60.1/23.7  | 61.2/24.1  | 62.4/24.6  |
| <b>M</b> HEAD TUBE LENGTH (CM/IN)      | 10.7/4.2  | 11.5/4.5  | 12.5/4.9  | 13.9/5.5  | 15.5/6.1  | 17.5/6.9   | 19.5/7.7   | 21.9/8.6   |
| <b>N</b> STACK (CM/IN)                 | 51.6/20.3 | 52.6/20.7 | 53.6/21.1 | 55.1/21.7 | 56.7/22.3 | 58.4/23.0  | 60.3/23.7  | 62.6/24.7  |
| <b>O</b> REACH (CM/IN)                 | 36.9/14.5 | 37.5/14.7 | 38.1/15.0 | 38.7/15.2 | 39.3/15.5 | 39.9/15.7  | 40.5/15.9  | 41.1/16.2  |

